



Paint Recycling, Inc.
"Quality Remade"

2010 Interior /Exterior Envirotex Finish Coat

CHARACTERISTICS:

- Remanufactured
- Contains a minimum of 50% post-consumer paint
- Uniform Finish
- Spray Application
- Weather Resistant
- Low Odor
- High Strength
- Available in flat and Eggshell finishes
- Three textures available (fine, medium, coarse)
- Self-Priming finish coat for most surfaces (priming with Visions SE-2000 or equivalent is recommended for "difficult to adhere" substrates)
- Water clean up

APPLICATION SUBSTRATES

Concrete
Precast panels
Masonry
CMU Construction
Primed Wallboard Surfaces

MILDEW RESISTANT:

This coating contains agents that inhibit the growth of mildew on the surface of this coating.

DRYING TIME:

To Touch ----- 30-60 minutes
To Re-coat ----- 5-6 hours
Lower temperatures, humidity, thicker film or improper ventilation will increase these times.

**This product tends to hide minor imperfections in the substrate. Good for adding interest to otherwise smooth surfaces.

PHYSICAL PROPERTIES

Finish: Flat Sheen @ 60° ----- 2-6
Eggshell @ 60°----- 7-14

VOLUME SOLIDS:
Approximately 35-40
WEIGHT SOLIDS:
Approximately 48-55

COLORS:
Available in interior and exterior stock colors.
VISCOSITY:
Package Viscosity 90-100 KU

Recommended Dry Film Thickness:
1.5 to 1.8 Mills DFT per coat

PREPARATION AND PRIMING APPLICATION

BLOCK: (Prime with appropriate primer)
Allow new block to cure before Application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, efflorescence, grease, oil, wax, mildew or other foreign matter.

CONCRETE:
Allow new concrete to cure for 60 days before application of primer and finish coats. Patch all voids with the appropriate patching or caulking material. Power-wash all tilt-up and poured in place concrete to remove any bond-breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

METAL: (Prime with appropriate primer)
Apply finish to primed or previously painted metal with no visible rust. Scrape, power tool, clean and sand the surface to remove any dirt, grease, oil, rust, mill scale, loose shop primer or other foreign matter.

STUCCO:
Allow new stucco to cure before application of finish coats. Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material. Best results are obtained when surface is back-rolled.

WOOD:
Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

PREVIOUSLY PAINTED SURFACES:
Patch all voids with the appropriate patching or caulking material. Wash, rinse, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

PERFORMANCE PROPERTIES:
Approximately 100-150 sq. ft. per gallon depending on substrate and application method, porosity and surface texture. Approximate coverage for each coat.

METHODS:
Spray with textured sprayer maintaining a "wet edge" and apply coating uniformly.

THINNING:
Product intended for use at package Consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:
Clean up equipment and area with soapy water.

APPLICATION:
Do not apply where material, air or surface Temperature is below 50° F Surfaces and ambient temperatures must be between 48° F and 100° F, 5° above dew point and remain above 48° F for a minimum of four hours after application. All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:
Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

MEETS GREEN SEAL GS 43

STORAGE:
KEEP FROM FREEZING STORE ABOVE 50° F

MAXIMUM VOC:
<150 GRAMS PER LITER

CAUTION:
Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet (MSDS)

KEEP OUT OF REACH OF CHILDREN.
USE ONLY WITH ADEQUATE VENTILATION

© Copyright VRI, Inc. 2013 All rights reserved Internationally
Visions Recycling, Inc. 4105 South Market Court • Suite A, Sacramento, CA 95834
Toll Free: 800-770-7664 / Phone: 916-564-9121 / Fax: 916-568-1485

www.visionsrecycling.com

VRI 100 PDS Revision: 08-26-2014