



PLV-200 Interior Low Voc Latex Primer

CHARACTERISTICS:

- Remanufactured
- Contains a minimum of 50% post-consumer primer
- Excellent Adhesion
- General Purpose
- Durable
- Easy Application
- Soap & Water Clean-Up
- Low Odor

PHYSICAL PROPERTIES:

- Finish: Flat
- Sheen @ 60° ----- 2-6%

VOLUME SOLIDS:

- Approximately 35%

COLORS:

Can be tinted to colors.

VISCOSITY:

Package Viscosity 85-100 KU

PERFORMANCE PROPERTIES:

Approximately 300-400 sq. ft. per gallon depending on substrate and application method, porosity and surface texture. Approximate coverage for each coat.

Recommended Dry Film Thickness:

- 1.5 to 1.7 MILS DFT

MILDEW RESISTANT:

This coating contains agents that inhibit the growth of mildew on the surface of this coating.

DRYING TIME:

To Touch ----- 30-60 minutes

To Re-coat ----- 5-6 hours

Lower temperatures, humidity, thicker film or improper ventilation will increase these times.

PREPARATION & PRIMING APPLICATION:

DRYWALL:

Allow new drywall finishes to dry before application of primer and finish coats. Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, dust, grease, mildew, oil, wax, and other foreign material.

METHODS:

Product may be applied with brush, roller or airless sprayer. Maintain a "wet edge" and apply coating uniformly.

THINNING:

Product intended for use at package Consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:

Clean up equipment and area with soapy water.

Application:

Do not apply where material, air or surface Temperature is below 50° F Surfaces and ambient temperatures must be between 48° F and 100° F, 5° above dew point and remain above 48° F for a minimum of four hours after application. All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING STORE ABOVE 50° F

MAXIMUM VOC:

<50 GRAMS PER LITER

CAUTION:

Avoid contact with eyes, skin and clothing. Do not take internally.

Wash thoroughly after handling.

Close container after each use.

For additional safety information consult the Material Safety Data Sheet (MSDS)

KEEP OUT OF REACH OF CHILDREN.

USE ONLY WITH ADEQUATE VENTILATION.