

TECHNICAL DATA SHEET

Visions High Performance Primer 800 WORKHORSE[™] Latex Paint

High quality water-based, stain blocking, undercoat that works on both interior and exterior surfaces.

- | | |
|---|--|
| <ul style="list-style-type: none"> • EXCELLENT QUALITY • EXCELLENT ADHESION • EASY APPLICATION • BLOCKS WATER STAIN | <ul style="list-style-type: none"> • WEATHER RESISTANT • HIGHLY DURABLE • WATER BASED |
|---|--|

PERFORMANCE PROPERTIES

Covers approximately 300–400 Sq. Ft. per gallon depending on the substrate and application method, porosity and surface texture.

Recommended Dry Film Thickness:

- 1.5–1.7 Mils DFT per coat

DRYING TIME

To touch: 30–60 minutes

To Re-coat: 5-6 hours

Lower temperatures, humidity, thicker film or improper ventilation will increase these times.

Allow 7–10 days before washing or scrubbing.

PREPARATION & PRIMING

BLOCK: Allow new block to cure before Application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, grease, efflorescence, oil, wax, mildew or other foreign matter.

CONCRETE: Allow new concrete to cure for 60 days before application of primer and finish coats. Patch all voids with the appropriate patching or caulking material. Power-wash all tilt-up and poured in place concrete to remove any bond breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

STUCCO: Allow new stucco to cure before application of finish coats. Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material. Best results are obtained when surface is backer rolled.

WOOD: Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

REMOUSLY PAINTED SURFACES:

Patch all voids with the appropriate patching or caulking material. Wash, rinse, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

DIRECTIONS FOR USE

METHODS:

Product may be applied with brush, roller or airless sprayer. Maintain a 'wet edge' and apply coating uniformly.

THINNING:

Product intended for use at package Consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEANUP:

Clean up equipment and area with soapy water.

APPLICATION:

Do not apply when material, air or surface Temperature is below 50°F Surfaces and ambient temperatures must be between 48°F and 100°F, 5°F above dew point and remain above 48°F for a minimum of four hours after application. All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING STORE ABOVE 50°F

MAXIMUM VOC: <50 GRAMS PER LITER

CAUTION:

- Avoid contact with eyes, skin and clothing
- Do not take internally.
- Wash thoroughly after handling
- Close container after each use.
- For additional safety information consult the Safety Data Sheet (SDS)

Safety Data Sheet

KEEP OUT OF REACH OF CHILDREN

USE ONLY WITH ADEQUATE VENTILATION