



TECHNICAL DATA SHEET

Visions Interior/Exterior 1100 Flat WORKHORSE™ Latex Paint

Visions Interior/Exterior Workhorse™ Latex Paint delivers remarkable hide and provides a non-reflective, matte finish.

- EXCELLENT QUALITY
- MILDEW RESISTANT
- EASY APPLICATION
- ENVIRONMENTALLY FRIENDLY
- EXCELLENT ADHESION
- HIGHLY DURABLE
- WATER BASED

PERFORMANCE PROPERTIES

Covers approximately 300 – 400 Sq. Ft. per gallon depending on the substrate and application method, porosity and surface texture.

Recommended Dry Film Thickness:

- 1.5 – 1.7 Mils DFT per coat

DRYING TIME

To touch: 30 – 60 minutes

To Re-coat: 5 – 6 hours

Lower temperatures, humidity, thicker film or improper ventilation will increase these times.

Allow 7 – 10 days before washing or scrubbing.

PREPARATION & PRIMING

BLOCK: (Prime with appropriate primer) Allow new block to cure before Application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, grease, efflorescence, oil, wax, mildew or other foreign matter.

CONCRETE: (Prime with appropriate primer) Allow new concrete to cure for 60 days before application of primer and finish coats. Patch all voids with the appropriate patching or caulking material. Power-wash all tilt-up and poured in place concrete to remove any bond-breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

METAL: (Prime with appropriate primer) Apply finish to primed or previously painted metal with no visible rust. Scrape, power tool, clean and sand the surface to remove any dirt, grease, oil, rust, mill scale, loose shop primer or other foreign matter.

WOOD: (Prime with appropriate primer) Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

REVIOUSLY PAINTED SURFACES:

Patch all voids with the appropriate patching or caulking material. Wash, rinse, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

DIRECTIONS FOR USE

METHODS:

Product may be applied with brush, roller or airless sprayer. Maintain a "wet edge" and apply coating uniformly.

THINNING:

Product intended for use at package Consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:

Clean up equipment and area with soapy water.

APPLICATION:

Do not apply when material, air or surface Temperature is below 50°F Surfaces and ambient temperatures must be between 48°F and 100°F, 5°F above dew point and remain above 48°F for a minimum of four hours after application. All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING STORE ABOVE 50°F

MAXIMUM VOC: <50 GRAMS PER LITER

CAUTION:

- Avoid contact with eyes, skin and clothing.
- Do not take internally.
- Wash thoroughly after handling.
- Close container after each use.
- For additional safety information consult the Safety Data Sheet (SDS)

KEEP OUT OF REACH OF CHILDREN.

USE ONLY WITH ADEQUATE VENTILATION.



TECHNICAL DATA SHEET

Visions Interior | Exterior 1200 Eggshell WORKHORSE™ Latex Paint

Visions Interior | Exterior Workhorse™ Latex Paint delivers remarkable hide and provides a low luster finish.

- | | |
|---|---|
| <ul style="list-style-type: none"> • EXCELLENT QUALITY • MILDEW RESISTANT • EASY APPLICATION • ENVIRONMENTALLY FRIENDLY | <ul style="list-style-type: none"> • EXCELLENT ADHESION • HIGHLY DURABLE • WATER BASED |
|---|---|

PERFORMANCE PROPERTIES

Covers approximately 300 – 400 Sq. Ft. per gallon depending on the substrate and application method, porosity and surface texture.

Recommended Dry Film Thickness:

- 1.5 – 1.7 Mils DFT per coat

DRYING TIME

To touch: 30 – 60 minutes

To Re-coat: 5 – 6 hours

Lower temperatures, humidity, thicker film or improper ventilation will increase these times.

Allow 7 – 10 days before washing or scrubbing.

PREPARATION & PRIMING

BLOCK: (Prime with appropriate primer) Allow new block to cure before Application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, grease, efflorescence, oil, wax, mildew or other foreign matter.

CONCRETE: (Prime with appropriate primer) Allow new concrete to cure for 60 days before application of primer and finish coats. Patch all voids with the appropriate patching or caulking material. Power-wash all tilt-up and poured in place concrete to remove any bond-breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

METAL: (Prime with appropriate primer) Apply finish to primed or previously painted metal with no visible rust. Scrape, power tool, clean and sand the surface to remove any dirt, grease, oil, rust, mill scale, loose shop primer or other foreign matter.

WOOD: (Prime with appropriate primer) Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

REVIOUSLY PAINTED SURFACES:

Patch all voids with the appropriate patching or caulking material. Wash, rinse, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

DIRECTIONS FOR USE

METHODS:

Product may be applied with brush, roller or airless sprayer. Maintain a "wet edge" and apply coating uniformly.

THINNING:

Product intended for use at package Consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:

Clean up equipment and area with soapy water.

APPLICATION:

Do not apply when material, air or surface Temperature is below 50°F Surfaces and ambient temperatures must be between 48°F and 100°F, 5°F above dew point and remain above 48°F for a minimum of four hours after application. All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING STORE ABOVE 50°F

MAXIMUM VOC: <50 GRAMS PER LITER

CAUTION:

- Avoid contact with eyes, skin and clothing.
- Do not take internally.
- Wash thoroughly after handling.
- Close container after each use.
- For additional safety information consult the Safety Data Sheet (SDS)

KEEP OUT OF REACH OF CHILDREN.

USE ONLY WITH ADEQUATE VENTILATION.



TECHNICAL DATA SHEET

Visions Interior/Exterior 1300 Semi-Gloss WORKHORSE™ Latex Paint

Visions Interior/Exterior Workhorse™ Latex Paint delivers remarkable hide and provides a radiant shiny finish.

- EXCELLENT QUALITY
- MILDEW RESISTANT
- EASY APPLICATION
- ENVIRONMENTALLY FRIENDLY
- EXCELLENT ADHESION
- HIGHLY DURABLE
- WATER BASED

PERFORMANCE PROPERTIES

Covers approximately 300 – 400 Sq. Ft. per gallon depending on the substrate and application method, porosity and surface texture.

Recommended Dry Film Thickness:

- 1.5 – 1.7 Mils DFT per coat

DRYING TIME

To touch: 30 – 60 minutes

To Re-coat: 5 – 6 hours

Lower temperatures, humidity, thicker film or improper ventilation will increase these times.

Allow 7 – 10 days before washing or scrubbing.

PREPARATION & PRIMING

BLOCK: (Prime with appropriate primer) Allow new block to cure before Application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, grease, efflorescence, oil, wax, mildew or other foreign matter.

CONCRETE: (Prime with appropriate primer) Allow new concrete to cure for 60 days before application of primer and finish coats. Patch all voids with the appropriate patching or caulking material. Power-wash all tilt-up and poured in place concrete to remove any bond-breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

METAL: (Prime with appropriate primer) Apply finish to primed or previously painted metal with no visible rust. Scrape, power tool, clean and sand the surface to remove any dirt, grease, oil, rust, mill scale, loose shop primer or other foreign matter.

WOOD: (Prime with appropriate primer) Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

REVIOUSLY PAINTED SURFACES:

Patch all voids with the appropriate patching or caulking material. Wash, rinse, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

DIRECTIONS FOR USE

METHODS:

Product may be applied with brush, roller or airless sprayer. Maintain a "wet edge" and apply coating uniformly.

THINNING:

Product intended for use at package Consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:

Clean up equipment and area with soapy water.

APPLICATION:

Do not apply when material, air or surface Temperature is below 50°F Surfaces and ambient temperatures must be between 48°F and 100°F, 5°F above dew point and remain above 48°F for a minimum of four hours after application. All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING STORE ABOVE 50°F

MAXIMUM VOC: <50 GRAMS PER LITER

CAUTION:

- Avoid contact with eyes, skin and clothing.
- Do not take internally.
- Wash thoroughly after handling.
- Close container after each use.
- For additional safety information consult the Safety Data Sheet (SDS)

KEEP OUT OF REACH OF CHILDREN.

USE ONLY WITH ADEQUATE VENTILATION.